



MINI
HDMI to CVBS

USER Manual

Table of Contents

1.0 Introduction

2.0 Specifications

3.0 Package Contents

4.0 Panel Descriptions

5.0 Connection Diagram

1.0 Introduction

The MINI HDMI to AV signal converter which will convert HDM video signal or audio signal to AV (CVBS) composite video signal and the FL / FR stereo audio signals, while support DVI system sideline signals. To help users convert the high quality of the HDMI video signal into normal CVBS signal (standard-definition 480i, 576i,).So that can play on TV, VHS VCR, DVD recorders, etc and support NTSC and PAL two TV format.

1.1 Features

1. No need to install drivers, portable, flexible, plug and play.
2. Low power, No power adaptor.

3. Support NTSC and PAL two standard TV formats

output

4. Compatible HDMI1.3

2.0 SPECIFICATIONS

1. Input ports: 1xHDMI.

2. Output ports: 1xRCA (Yellow, White, Red)

3. Dimensions (mm): 66(D) x55(W) x20(H)

4. Wight (g): 40

5. HDMI Input Resolution:

640x480@60Hz,800x600@60Hz,

1024x768@60Hz,1280x720@60Hz,

1280x1024@60Hz,1360x768@60Hz,

1600x1200@60Hz,1920x1080@60Hz,

480i/60Hz, 480p/60Hz, 576i/60Hz, 576p/60Hz,

720p50/60Hz,1080I50/60Hz, 1080p50/60Hz.

6. CVBS output: PAL, NTSC_M, and (NTSC_J)

3.0 PACKAGE CONTENTS

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- 1) Main unit (HDMI to AV Converter) -----1PCS
- 2) USB Cable-----1PCS
- 3) User Manual. -----1PCS

4.0 PANEL DESCRIPTIONS

Please study the panel drawings below and become familiar with the signal input(s), output(s) and power requirements.

Back Panel:



Top Panel:



Front Panel



5.0 CONNECTION DIAGRAM



Errors and omissions excepted.

Copyright© 2021 AVSL Group Ltd, Unit 2 Bridgewater Park,
Taylor Road, Trafford Park, Manchester. M41 7XQ.

AVSL (Europe) Ltd, Unit 3D North Point House,
North Point Bus. Park, New Mallow Road, Cork, Ireland.