

1x4 Stereo Audio Distribution Amplifier

Model : SB-3705


Instruction Manual

Shinybow®

4 Stereo Audio Distribution Amplifier

4x Ways Stereo Audio


1 input > 4 outputs



Model : SB-3705

Input : Stereo Audio AR/AL (RCA connectors)

Output : 4 x Stereo Audio AR/AL (RCA connectors)

Power Input : DC +12V, 100mA ~ 500mA. 

Safety Notice!

To prevent damage to your television equipment use only the supplied AC Adaptor and make the power connections to your television.

Stereo Audio Distribution Amplifier Series

Thank you for purchasing the SB-3705 Stereo Audio 4 Ways Splitter. You will find this unit easy to install and highly reliable but it is essential that you read this manual thoroughly before attempting to use switcher.


129 574

Supplied Accessories

Check that you have the following components in your converter pack :

- (1) 1 Instruction Manual
- (2) 1 SB-3705 module
- (3) 1 Audio Cable (RCA-RCA connector)
- (4) 1 AC Adaptor : 12VDC, 300mA ~ 500mA

Video Connecting Cable : AC/DC Adaptor : CE/UL/SA/ABS
2RCA-2RCA plug, L=6FT



Introduction

Congratulations on your purchase of one of the most innovative Stereo Audio signal distribution product on the market today. Choose the 4 outputs SB-3705. This product provide multiple Stereo Audio outputs that are identical to the Audio source signal. This is useful for distributing Stereo Audio signals from VCRs, Camcorders, Video Game Consoles, Video CDs, DVDs, Satellite Receivers, CATV Set Top Boxes, etc.

Before you make any connections

Make sure all Composite Video devices to be connected to the composite Video Splitter are functioning according to their respective operation manuals before connecting them. Always connect the composite Video devices to the composite Video Distribution Amplifier one at a time and make sure each works just as it did before it was connected.

Safeguards and Precautions

- a . Keep this unit away from fire, extremely hot areas, water or moisture of any kind.
- b . Do not place this unit on any support that is not firm, level and strong.
- c . Do not service the unit yourself. Opening the unit's housing will void the warranty.
- d . Servicing must be by Shinybow or by an authorized technician.
- e . Illegal duplication of copyrighted material is strictly prohibited by Federal Laws.


Specifications

Model Number	SB-3705
Audio Inputs	Composite Video, 75Ω on RCA connector.
Audio Outputs	4xStereo Audio, AR/AL 47Ω
Audio Bandwidth	20Khz ~ 50Khz
Audio Distortion	<0.6db (+/- 3db)
Power Consumed	100mA Maximum
Power Source	DC +12 Volts , @300~500mA

Typical Hookup and Operation




Front View:
Power sw : ON/OFF



Rear View:
Input : Stereo Audio(R/L)
Outputs : 4xStereo Audio(R/L)
DC Input : 12V, 300~500mA

4 x Stereo Audio Distribution Amplifier Stereo Audio system: RCA connectors



129574