

CX-5008

SPEAKER CABINET

Order ref: 170.211

User Manual



Full range speaker enclosure made from premium Russian ply with custom drive units giving a wide bandwidth and smooth response for all styles of programme material.

Multiple flying points are fitted as standard for ease of installation and integration into arrays.


Computer-aided design for optimal tuning of enclosures delivering efficient output and bottom end response with strategic bracing to reduce resonance and improve projection.

- Durable textured black paint finish
- 12 x M10 flying points
- Powder-coated steel grille lined with dust filter
- Active electronic protection fitted to prevent overload to H.F. units
- Crossovers optimized for balanced integration of drivers
- Speakon® connectors fitted
- 35mm pole mount socket
- All fittings rebated for easier stacking and arraying
- Steel bar handles fitted as standard

Specifications


Power RMS	500W
Power Max	800W (5 minutes max)
LF driver	380mmØ (15")
HF driver	Compression driver with 72mmØ titanium diaphragm
Impedance	8Ω
Frequency response (-3dB)	45Hz - 18KHz
Frequency response (-10dB)	40Hz - 20KHz
Sensitivity (1W/1m)	97dB
Dispersion (H x V)	90° x 40°
Connectors	2 x Speakon® (NL 4)
Dimensions	805 x 500 x 500mm
Weight	43.5kg

Technical drawings




Technical Diagrams


Frequency response - Magnitude




Impedance - Magnitude



Distortion - Magnitude



Combination - Magnitude



Connection

