

citronic

Column Arrays

Our Column Array series delivers full-range, high-quality sound in compact, modular systems.

The Monolith mk3 features a 500W active sub with USB/SD and Bluetooth for flexible mono or stereo setups, while the Neolith mk2 offers a compact sub with neodymium drivers, DSP control, and fast pole-mounted assembly - ideal for live PA, events, and mobile performances.



PRODUCT NAME	MONOLITH SUB + COLUMN ARRAY	NEOLITH MK2 SUB + COLUMN SET
Item Code	171.237UK	171.238UK
Output Power : rms	400W + 100W	400W
Output Power : max	1000W	800W
Power Supply	230Vac, 50Hz(IEC)	
Main Driver	Column drivers - 4 x 100mmØ (4") Ferrite, 1 x 25mmØ (1") Neodymium	Column drivers - 4 x 90mmØ (3.5") Neodymium 1 x 25mmØ (1") Neodymium
Frequency Response	35Hz - 20kHz	55Hz - 20kHz
SPL Max	Sensitivity: 103dB	Sensitivity: 94dB
Amplifier	500W class-D bi-amplifier	Class-D bi-amplifier
Bluetooth	Internal USB/SD/BT player	Built-in Bluetooth receiver
Mic Inputs	Switchable Mic (XLR/Jack)	
Line Inputs	Line (Jack/RCA)	
Line Output	Speaker out (SPK) to column, Line out (XLR)	Line out (XLR)
DSP Input Control	Yes	5 x preset tone profiles
Mounting Points	35mm Speaker Pole	
Construction	15mm MDF with texture polyurea coating	
Dimensions	Sub Cabinet: 480 x 450 x 380mm Column: 580 x 140 x 115mm	Sub Cabinet: 450 x 400 x 320mm Column: 520 x 143 x 111mm
Weight	Sub Cabinet: 20kg Column: 5.6kg	Sub Cabinet: 15.95kg Column: 2.95kg
In The Box	Monolith mk3 active subwoofer & Monolith mk3 passive column speaker & adjustable 35mmØ mounting pole & SPK-SPK link lead & IEC power lead	10" active sub cabinet & 4 x 3.5" satellite column array & mounting and connection pole & S lip cover (sub cabinet) & Carry bag (column & pole) & IEC power lead
Application Scenarios	All-in-one active sub and column array stack, easy to carry with no need for separate cabinets. Perfect for solo performers and small events.	Perfect for medium to high volume PA applications, Neolith mk2 sets up fast, fills rooms with clear bass-driven sound easily.