

Stage Monitors

Our CM Series stage monitors delivers clear, focused foldback for performers, available in both active and passive versions to suit any setup.

Designed for reliability and clarity on stage, these monitors provide the power, control and durability needed for live shows, rehearsals and touring environments.



| PRODUCT NAME | CM10A ACTIVE WEDGE | CM12A ACTIVE WEDGE | CM15A ACTIVE WEDGE | CM10 PASSIVE WEDGE | CM12 PASSIVE WEDGE | CM15 PASSIVE WEDGE |
|-----------------------|--|---|---|---|---|---|
| Item Code | 178.690UK | 178.692UK | 178.695UK | 178.691UK | 178.693UK | 178.696UK |
| Output Power : rms | 250W | 300W | 350W | 250W | 300W | 350W |
| Output Power : max | 400W | 600W | 700W | 450W | 600W | 700W |
| Power supply | 230Vac, 50Hz (IEC) | - | - | 230Vac, 50Hz (IEC) | - | - |
| Main Driver | 250mmØ (10") with concentric tweeter, 50mmØ (2") voice coil | 300mmØ (12") with concentric tweeter, 75mmØ (2.5") voice coil | 380mmØ (15") with concentric tweeter, 75mmØ (2.5") voice coil | 250mmØ (10") coaxial with voice coil 50mmØ (2") | 300mmØ (12") with voice coil 63mmØ (2.5") | 380mmØ (15") with voice coil 63mmØ (2.5") |
| Frequency Response | 65Hz - 20kHz | 55Hz - 20kHz | 45Hz - 20kHz | 65Hz - 20kHz | 55Hz - 20kHz | 45Hz - 20kHz |
| SPL Max | Sensitivity: 95dB | Sensitivity: 96dB | Sensitivity: 97dB | Sensitivity: 95dB | Sensitivity: 96dB | Sensitivity: 97dB |
| Amplifier | Class-D Bi-Amplifier | - | - | Yes | - | - |
| Bluetooth | Built-in Bluetooth Receiver | | | | | |
| Mic Inputs | 1x Mic/Line (XLR/Jack combo) | | | | | |
| Line Inputs | Line (XLR/jack/RCA) | | | | | |
| Line Output | Headphones (6.35mm jack), Mix out (XLRM) | | | | | |
| DSP Input Control | 5 Preset Modes (Normal, DJ, Voice, Live, Flat) | | | | | |
| Mounting Points | 35mm pole mount socket and M8 flying points | | | | | |
| Construction | Texture coated wooden cabinet + arched powder-coated steel grille | | | | | |
| Dimensions | 355 x 350 x 275mm | 445 x 410 x 335mm | 528 x 504 x 382mm | 355 x 350 x 275mm | 445 x 410 x 335mm | 528 x 504 x 382mm |
| Weight | 9.87kg | 12.10kg | 15kg | 8.64kg | 10.80kg | 13.30kg |
| In The Box | CM10A Active Wedge Speaker + IEC mains lead | CM12A Active Wedge Speaker + IEC mains lead | CM15A Active Wedge Speaker + IEC mains lead | CM10 Passive Wedge Speaker | CM12 Passive Wedge Speaker | CM15 Passive Wedge Speaker |
| Application Scenarios | CM active wedges provide quick, self-powered monitoring for small to medium stages, rehearsals and mobile setups, delivering clear foldback for singers, musicians and presenters. | | | CM passive wedges suit venues using external amplifiers, offering reliable foldback for bands, theatres and touring systems needing multiple mixes and consistent stage monitoring. | | |