

Introduction

Lyyt Seamless COB LED Strip provides a continuous 'no spot' linear lighting solution. The COB (chip on board) technology consists of 840 tightly packed LED's per metre and a phosphor layer coating which diffuses the LED's into a seamless array of light. The flexible COB strip is supplied on a 5m reel and can be cut to desired length along the designated cutting points, the strip is equipped with an adhesive backing for easy installation. The 24Vdc COB strip is suitable for a wide variety of applications, such as hospitality, retail, offices, displays, exhibitions and more. IP20 versions are for indoor use only.


Specification

Voltage	24Vdc
Beam angle	160°
Reel Length	5m
IP Rating	IP20
Power consumption per metre	14W
Current	583mA per metre
LED quantity per metre	840
Cut points	50 mm

Installation of this COB Strip should be carried out by competent electrical installers, observing the relevant electrical safety procedures. Lyyt COB Strip has a self-adhesive backing to allow it to be easily attached to a clean, non-porous surface.

Where less than 5m of tape is needed, there are solder points as shown below, where the tape may be cut to size. These cut points are at 5cm intervals. To re-connect to another length of tape after cutting, solder a wire from “+” to “+” and a wire from “G”, “R” and “B” as shown below. Some accessories are supplied with the tape reel for this purpose.

Alternatively, you can use solderless connectors to achieve this result. For best protection of this tape, we recommend inserting the tape into one of our aluminium Profiles.



Each 5m reel of COB Strip has connectors to allow easy connection to an RGB controller and power input. If the power supply has enough capacity to power more than one reel, another reel can be connected to the end of the first reel. Using an amplifier repeater will ensure that extension reels mimic the colour changes and brightness of the original reel.

It is imperative that the power supply should have higher than the rated capacity in Amps (A) for the current required to power the length(s) of COB Strip installed.

Likewise, if controllers and amplifiers/repeaters are used, these must have adequate capacity for the tape being controlled. Please see the table below for reference.

Tape Length	5m	10m	15m	20m	25m
Current for 24V tape 840 LED/m	2.425A	4.85A	7.275A	9.7A	12.125A

Please visit www.avsl.com to select from our range of 24Vdc power supplies that are suitable for powering Lyyt COB Strip



This product is classed as Electrical or Electronic equipment and should not be disposed with other household or commercial waste at the end of its useful life. The goods must be disposed of according to your local council guidelines.

Errors and omissions excepted.

Copyright© 2025 AVSL Group Ltd, Unit 2 Bridgewater Park,
Taylor Road, Trafford Park, Manchester. M41 7JQ.

AVSL (Europe) Ltd, Unit 3D North Point House,
North Point Bus. Park, New Mallow Road, Cork, Ireland.