

INSTRUCTION MANUAL



1 INTRODUCTION

Thank you for buying HUBSAN products. The Q4 Nano quad is designed as an easy-to-use, full-featured RC model capable of hovering and aerobatic flight maneuvers. Please read the manual carefully and follow all instructions in it. Be sure to retain the manual for future reference, routine maintenance and tuning.

2 SAFETY NOTES

2.1 Important Notes
This RC Nano quad is not a toy.
Any improper use of this product will result in serious injury. Be aware of your personal safety, safety of others and your surrounding environment.
We recommend beginners learn to fly with more experienced pilots playing nearby before attempting to fly the Q4 for the first time.

2.2 Caution
The Q4 Nano quad has parts that move at high speed, which poses a certain degree of danger.
Choose a wide open space without obstacles. Do not operate the Q4 near buildings, crowds of people, high voltage cables, or wires to ensure the safety of yourself, others and your model.
Improper operation may cause damage to people and property.

2.3 LiPo Battery Safety Notes
The Q4 is powered by a Lithium Polymer (LiPo) battery.
If you do not plan to fly the Q4 for a week or more, store the battery approximately 50% charged to maintain battery performance and life.

SAFETY ADVISORY NOTICE
Lithium-Polymer (LiPo) Batteries

LiPo batteries are different from conventional batteries in that their chemical contents are enclosed in a relatively lightweight foil packaging. This has the advantage of significantly reducing their weight, but does make them more susceptible to damage if roughly or irresponsibly handled. As with all batteries, there is a risk of fire or explosion if safety processes are ignored.

- ⚠ Charge and store LiPo batteries in a location where a battery fire or explosion (including smoke hazard) will not endanger life or property.
- ⚠ Keep LiPo batteries away from children and animals.
- ⚠ Never charge the LiPo battery that has ballooned or swelled.
- ⚠ Never charge the LiPo battery that has been punctured or damaged.
- ⚠ After a crash, inspect the battery pack for the sign of damage. Discard in accordance with your country's recycling laws.
- ⚠ Never charge the LiPo battery in a moving vehicle.
- ⚠ Never overcharge the LiPo battery.
- ⚠ Never leave the LiPo battery unattended during recharging.
- ⚠ Do not charge LiPo batteries near flammable materials or liquids.
- ⚠ Ensure that charging leads are connected correctly. Reverse polarity charging can lead to battery damage or a fire or explosion.
- ⚠ Have a suitable fire extinguisher (electrical type) Q4 in a large bucket of dry sand near the charging area. Do not try to extinguish electrical LiPo battery fires with water.
- ⚠ Reduce risks from fire/explosion by storing and charging LiPo batteries inside a suitable container.
- ⚠ Protect your LiPo battery from accidental damage during storage and transportation. (Do not put battery packs in pockets or bags where they can drop out or can come into contact with sharp or metallic objects.)
- ⚠ If your LiPo battery is subjected to a shock (such as a crash), place it in a metal container and observe for signs of swelling or heating for at least 30 minutes.
- ⚠ Do not attempt to disassemble or modify or repair the LiPo battery.

2.4 Prevent Moisture

The Q4 contains many precision electrical components.
Store the battery and the Q4 in a dry area at room temperature. Exposure to water or moisture may cause malfunction resulting in loss of responsiveness, or a crash.

2.5 Proper Operation

For safety only use the included HUBSAN spare parts for replacement.

2.6 Always Be Aware of the Rotating Blades

When in operation, the main and tail rotor blades will be spinning at high speeds. The blades are capable of inflicting serious body injury or damage to property.
Be careful to keep your body and loose clothing away from the blades. Never take your eyes off the Q4 or leave it unattended while it is turned on. Stop operation immediately if the Q4 flies out of your view. Once landed, immediately turn off the Q4 and transmitter.

2.7 Avoid Flying Alone

Beginners should avoid flying alone when learning flight skills. We recommend flying with an experienced pilot nearby in case you need help.

3 SAFETY CHECK BEFORE FLYING

CAREFULLY INSPECT THE Q4 BEFORE EVERY FLIGHT

- Before operation, check the batteries of the transmitter and Q4 are charged for the flight.
- Before turning on the transmitter, check that the throttle stick is pulled completely backward (down position).
- Carefully check rotor blades and rotor holders. Broken parts will pose a risk of injury and hazard.
- Check the battery and power plug are securely fastened. Reverse vibration during flight may detach the plug and result in loss of control.
- When turning on the unit, always turn on the transmitter first, and then turn on the Q4. To power off, always turn off the Q4 first, and then the transmitter. Improper procedure may cause loss of control of the nano quad.

4 Nano quad

4.1 Charge the Q4

Connect the battery with USB charger, then connect the USB charger to a computer or other USB connector, such as a smartphone charger. The LED lights up while charging and turns off when charging is complete. The voltage of the USB is $5\pm 0.2V$.

The nano quad is equipped with a 2.7V 100mAh LiPo battery.

4.2 Power on the Q4

5 TRANSMITTER

5.1 Identification and functions of the Main Menu TRANSMITTER

6 START TO FLY

6.1 Power-On (Failure) Procedure

Your Q4's flight controller is designed with a Power-On safety feature that ensures the Q4's motor will not start unless it directly receives a suitable motor control signal when the Q4 and the transmitter both power on and guard.

6.1.1 Make sure the throttle stick is in the full down position.

6.2 Transmitter Sticks And Q4 Control Response

CAUTION: To avoid loss of control, always move the transmitter sticks slowly. Be aware that control inputs will receive available lift. Be ready to use a little extra throttle to maintain height during maneuvers.

Throttle increases/decreases the flying height of your Nano quad.

7 Sensitivity Setup

The nano Q4 can perform in 3 stages: low-middle-high.

Click the elevator stick to enter the 3 different stages:

The LED on the transmitter is Solid Green in the Q4 is in the low stage (about 30% sensitivity).

The LED on the transmitter is blinking green - the Q4 is in the middle stage (about 50% sensitivity).

The LED on the transmitter is blinking orange - the Q4 is in the high stage (about 100% sensitivity).

Press the Elevator Trim (3) Aileron Trim to change the sensitivity values and then hold down the elevator stick for 1 second to confirm or exit. The Q4 will be more sensitive and responsive with the corresponding values.

8 Aerial Flip Tips

The flip will only work in HIGH-STAGE, press the elevator stick to switch into the High Stage.

Flipper rotates your Nano quad's fuselage left or right.

Elevator moves your Nano quad forward and backward.

Left movement, Right movement.

Aileron moves your Nano quad left and right.

8.1 Left Flip

Push the Aileron stick fully to the right and then quickly push it fully to the left. Release the stick to the center position after the flip.

8.2 Right Flip

Push the Aileron stick fully to the left and then quickly push it fully to the right. Release the stick to the center after the flip.

8.3 Forward Flip

Push the Elevator stick backward and then quickly push it forward. Release the stick to the center after the flip.

8.4 Backward Flip

Push the Elevator stick forward and then quickly pull it backward. Release the stick to the center after the flip.

Press the Throttle stick to enter Flip Mode, indicated by two "beep". Press the Throttle stick again to exit Flip Mode, indicated by one "beep".

⚠ For proper flip execution, make sure the Q4 is close to level, within a 30° angle with the ground, and add throttle to climb before you perform a flip.

Note: when the Q4 battery is low, performing flip is not possible.

9 REPLACING PROPELLERS

The Q4's propellers are not identical. Each propeller is labeled with an A or B. When installing propellers, be certain to install as shown below. The Q4 will not fly, and will flip and crash if the propellers are not installed correctly.

Install Propellers: Push the propeller hub, align the hole to the motor shaft, and press it straight down firmly but gently.

ROTOR GUARD

The rotor guard will reduce the risk of damaging the quadcopter and rotor (prop) for beginners.

The tabs on each side of the rotor guard lock into the large opening on the canopy.

To ATTACH the rotor guard hold the quadcopter as shown, then hook in the front tabs FIRST, then the middle, and the rear tabs last.

To REMOVE the rotor guard hold the quadcopter as shown, then ease the guard to one side unhooking the rear tabs FIRST, then the middle and the front tabs last.

⚠ Take care when installing/removing the rotor guard to avoid damaging it. The canopy can be removed for easier access in the tabs. The rotor guard may get damaged in the event of a crash but this is not deemed a product defect. Flight time will be reduced when fixed.

Exploded View

No.	PART NAME	QTY	No.	PART NAME	QTY
1	Mini RX	1	6	Shell	1
2	G1.2 motor (clockwise)	2	7	White blade A	1
3	G1.2 motor (counter-clockwise)	2	8	White blade B	1
4	LiPo battery	1	9	Black blade A	1
5	motor supporter	4	10	Black blade B	1

H111 TROUBLESHOOTING

1. Transmitter and Q4 do not pair.
Check that the motor, canopy, body and props are all properly positioned. Throttle position needs to be fully minimized. Please do not move the transmitter sticks or turn during initial power on/landing.

2. Q4 not working well
(1) Battery voltage too low.
(2) Be-level.
(3) Land on to the ground with the throttle fully minimized for 3 seconds and take off again.

3. Unable to Flip
(1) Press the Elevator stick briefly to switch into high stage (transmitter LED blinks orange three "beep"). Please check Elevator Sensitivity Setup PE.
(2) Press the throttle stick to turn off the anti-flip.
(3) LiPo power is too low. Recharge the Q4.

4. Nano quad is shaking and main/propellers.
Check that the motor, canopy, body and props are all properly positioned.

5. Switching between low and high rates on the transmitter is difficult.
Press the elevator stick briefly to switch into high stage (transmitter LED blinks orange, three "beep").

6. Can not take off.
(1) Improper installation of the props. Props are marked with "A" (CW) and "B" (CCW). Please check the pictures below for the correct order.
(2) Improper installation of motors. Please check to make sure that each motor is installed in its correct position. There are two different types of motors with different motor wire colors. Please check the pictures below for the correct order.

7. One or more motors stop working
(1) Motor is damaged. Replace the motor.
(2) Rebuilder any broken motor connections.
(3) No FFT on the flight controller tools burnt. Replace the flight controller.

8. The Q4 always drifts to one direction.
Calibrate the accelerometer as follows.

H111 SPARE PART CHART

H111-01 Body Shell And Motor Supporter Set	H111-02 Rx Set	H111-03 Motor Set
H111-04 LiPo Battery Set	H111-05 Blades Set	H111-06 USB Charger Set
H111-10 Q4 Protection Cover	H111-07 Transmitter	H111-09 Crash Pack